

## Amendments to the Specification

Please replace paragraphs [0025] and [0026] with the following paragraphs:

[0025] Referring to FIG. 5, when the photographic apparatus is rotated clockwise from 330° approximately 300° (9 o'clock position) to approximately 90° (3 o'clock position) (based on 0° corresponding to the twelve o'clock position), the rotation angle  $[[\Theta]] \theta$  is less than or equal to approximately 150°. Consequently, when the photographic apparatus 160 is generally oriented in the direction "A" (which corresponds to approximately 90° position), the image created by the photographic apparatus 160 is correctly reproduced on the LCD screen 140 with respect to orientation. Also, when the rotation angle  $[[\Theta]] \theta$  is less than or equal to approximately 150° between the approximately 300° and approximately 90° positions, the magnetic flux sensor 210 and magnet 200 are not relatively approximate approximately positioned to each other.

[0026] However, when the photographic apparatus 160 is rotated counterclockwise from approximately 300° position to approximately 270° position (based on 0° corresponding to the twelve o'clock position and 270° corresponding to the nine o'clock position) so that the rotation angle  $[[\Theta]] \theta$  exceeds approximately 150°, the photographic apparatus 160 is inversely positioned between the approximately 300° and approximately 270° positions and faces the user (*i.e.*, the photographic apparatus 160 is directed in the same general direction "B" as the LCD screen 140 and corresponds to approximately 270° position), as shown in FIG. 6. Consequently, the image photographed by the photographic apparatus 160 is inverted since the rotation of the photographic apparatus 160 is more than approximately 150°. This results in the photographic apparatus 160 as being oriented upside-down. However, rotation of the photographic apparatus 160 also results in positioning the magnet 200 approximate to the magnetic flux sensor 210. ~~In~~ Upon detecting a magnetic flux density, the sensor 210 emits a signal to the printed circuit board 120, which inverts the image to be correctly reproduced on the LCD screen 140.